

# CMNC-205D

## 2 MP Box Camera

CMOS	Full HD	H.264 MJPEG
DWDR	BLC	PoE
MICRO SD CARD	AUDIO ALARM	Motion Detection



### ( Features )

- 1 / 2.8" Sony Exmor Camera
- Resolution 1920 X 1080
- Min. Illumination : 0,03 lux
- True Day & Night for surveillance 24 hours
- C/CS Mounting
- Motion Dedection / Private Masking
- Streaming H.264 / MJPEG
- Wide Dynamic Range 120db
- Video Streaming Control VBR, CBR
- Bi-directional Audio communications  
G.711A / G.711U
- PoE ( Power over Ethernet, IEEE 802.3af )

Model	CMNC-205D
Type	2 Megapixel SONY Exmor
Image Sensor	1/ 2.8" CMOS
Min.Illumination	0.03 lux/F1.2
ICR-IR Cut Filter	Yes
Privacy Mask	On/Off (max.4 areas)
Motion Detection	On/Off (max.4 areas)
WDR	Yes
Lens	C / CS Mounting
Compression method	H.264
Resolution	1920x1080@25fps or 1280x960@25fps or 1280x720@25fps
Bit rate	Main Stream: 500kbps-6Mbps Sub Stream: 50-1000kbps
Multi-stream	Triple Stream: Master stream:2MP@25fps/1.3MP@25fps/1MP@25fps; Sub-stream: Q720P@25fps; MJPEG stream: 1-5fps
Protocol	TCP/IPv4,IPv6 UDP, RTP, RTSP, HTTP, DHCP, SMTP, ONVIF, RTMP, FTP, NTP, DDNS, uPNP, ARP, ICMP, IGMP
Storage	SD Card (Max. 32G) / CMS / NVR
Alarm	Alarm input*1, Alarm output*1
Online User	16 users online same time (with 6 video streams)
Onvif	Onvif 2.2, Profile S
Power Supply	DC12V, PoE(IEEE802.3af)
Power Consumption	400mA
Operating Environment	-10°C - 50°C